

TMP-S3

1 GHz Hardline Digital Splitters



Features

- 5 MHz to 1 GHz Bandwidth performance
- Bidirectional power rating to 15 amps @ 30, 60 and 90 Vac provide compatibility with most systems
- Housing top stainless steel mounting hardware for easy installation
- Epoxy coated aluminum alloy housing with tongue in groove interface provides 100 dB effective EMI/RFI shielding reducing ingress/egress signals
- Extended connector collars provide shoulder for good heat shrink bonding, eliminating connector water migration extending life of housing
- Rotating internal seizing pins provide installation flexibility allowing installation options
- Performance tests conducted conforming with SCTE standards IPS TP-201, 202 and 203

Specification

TMP-S3	5-10 MHz	10-400 MHz	400-600 MHz	600-750 MHz	750-900 MHz	900-1000 MHz
Insertion Loss (In-Out) max.	4.0/7.5	3.9/7.4	4.8/7.9	4.9/8.2	5.2/8.4	5.4/8.7
Isolation (Out-Out) min	23	25	25	25	23	21
Return Loss - All Ports	17	18	18	17	17	17
EMI	100 dB					

Ordering Information

TMP-S2 2-Port 1GHz Digital Splitters

TMP-S3 3-Port 1GHz Digital Splitters